Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-109-0077

······ ·······························
Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
2.282 inches
Overall Height:
1.781 inches
Overall Width:
1.781 inches
Environmental Protection:
Pressure proof
Unthreaded Mounting Hole Diameter:
Between 0.142 inches and 0.157 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.370 inches and 1.380 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.370 inches and 1.380 inches
Distance From Mounting Shoulder To Front Face:
0.625 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
24-11 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
73.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid



Connector Locking Method: Externally threaded shell **Thread Length:** 0.500 inches Thread Size: 1.438 inches and 1.500 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper single mating end all contact groupings **Contact Surface Treatment:** Silver single mating end all contact groupings **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 6 single mating end 2nd contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact surface silver **Precious Material And Weight:** 0.045 silver grains, troy **Precious Material:** Silver **Thread Series Designator:** Unef and unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0