NSN 5935-00-109-0186

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-109-0186

View Online at https://aerobasegroup.com/nsn/5935-00-109-0186				
Body Style:				
Straight shape, internal coupling w/strain relief				
Body Length:				
1.969 inches				
Overall Diameter:				
1.281 inches				
Environmental Protection:				
Moisture resistant and salt water resistant and vibration resistant				
Cable Entrance Diameter:				
0.609 inches				
Mating End Quantity:				
1				
Contact Position Arrangement Style:				
16-26 single mating end				
Contact Removability:				
Nonremovable single mating end single contact grouping				
Contact Maximum Ac Voltage Rating In Volts:				
600.0 single mating end single contact grouping				
Polarization Method:				
Key, multiple key groove				
Insert Position In Deg:				
275.0				
Shell Type:				
Solid				
Connector Locking Method:				
Bayonet latch				
Connector Cable Strain Relief Method:				
Cable clamp				
Terminal Location:				
Back single mating end single contact grouping				
Contact Surface Treatment:				
Gold single mating end single contact grouping and copper single mating end single contact grouping				
Terminal Type:				
Solder well single mating end single contact grouping				
Shell Material:				
Aluminum alloy				
Shell Surface Treatment:				
Cadmium				
Shell Surface Treatment Specification:				
Qq-p-416, type 2, cl 3 federal specification single treatment response				

Included Contact Quantity:

26 single mating end single contact grouping

NSN 5935-00-109-0186

Electrical Plug Connector - Page 2 of 2



Inc	luded	Contact	Type:
	luucu	Contact	iypc.

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-26482 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0