

View Online at <https://aerobasegroup.com/nsn/5935-00-109-0518>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

0.938 inches

**Overall Diameter:**

0.438 inches

**Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Bnc all mating ends

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch and bayonet pin

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings

**Insert Material:**

Plastic tetrafluoroethylene all mating ends

**Contact Material Specification:**

Qq-c-530, comp a federal specification single material response all mating ends all contact groupings

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Included Contact Quantity:**

1 2nd mating end all contact groupings

**Included Contact Type:**

Coaxial socket 2nd mating end all contact groupings

**Precious Material And Location:**

Contact surface gold and shell surface silver

**Precious Material And Weight:**

0.010 gold grains, troy and 0.100 silver grains, troy

**Precious Material:**

Gold and silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0