NSN 5935-00-109-0687

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-109-0687 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 2.650 inches **Overall Height:** 0.670 inches **Overall Width:** 0.620 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** Between 2.401 inches and 2.411 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Position Arrangement Style:** 24w7 single mating end **Contact Removability:** Removable single mating end 1st contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping

Shell Surface Treatment:

Cadmium

NSN 5935-00-109-0687

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Shell Material Specification:

Qq-s-636 federal specification single material response

Insert Material Specification:

Mil-m-19833, type gdi-30 military specification single material response single mating end

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Mtg. Holes provi*ed withclinch nuts

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.017 gold grains, troy and 0.017 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.