

View Online at <https://aerobasegroup.com/nsn/5935-00-110-0131>

Body Style:

Rectangular shape

Overall Length:

0.438 inches

Overall Height:

0.781 inches

Overall Width:

0.250 inches

Unthreaded Mounting Hole Diameter:

Between 0.089 inches and 0.092 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

13.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

950.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

1330.0 single mating end all contact groupings

Polarization Method:

Contact

Connector Locking Method:

Friction

Operating Temperature Rating:

Between 55.0 degrees celsius and 200.0 degrees celsius

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic melamine single mating end

Terminal Type:

Solder well single mating end all contact groupings

Insert Material Specification:

Mil-m-14, type mme military specification single material response single mating end

Included Contact Quantity:

1 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end 1st contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.002 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.