NSN 5935-00-110-0248

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-110-0248

Body Style:

Straight shape, external coupling

Overall Length:

Between 1.078 inches and 1.140 inches

Overall Height:

1.438 inches

Overall Width:

1.438 inches

Environmental Protection:

Shock proof and vibration resistant and humidity resistant and moisture resistant and corrosion resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.187 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.187 inches

Distance From Mounting Shoulder To Front Face:

0.531 inches

Mating End Quantity:

Contact Position Arrangement Style:

37-27p single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end 1st contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

150.0

Shell Type:

Connector Locking Method:

Friction

Connector Cable Strain Relief Method:

Compression nut

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

NSN 5935-00-110-0248

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Rubber synthetic single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification all treatment responses
Included Contact Quantity:
7 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end 1st contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.013 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):