# NSN 5935-00-110-0248

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-110-0248

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

Between 1.078 inches and 1.140 inches

**Overall Height:** 

1.438 inches

**Overall Width:** 

1.438 inches

#### **Environmental Protection:**

Shock proof and vibration resistant and humidity resistant and moisture resistant and corrosion resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

1.187 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.187 inches

#### **Distance From Mounting Shoulder To Front Face:**

0.531 inches

# **Mating End Quantity:**

# **Contact Position Arrangement Style:**

37-27p single mating end

# **Contact Removability:**

Removable single mating end all contact groupings

## **Contact Maximum Current Rating In Amps:**

7.5 single mating end 1st contact grouping

### **Polarization Method:**

Keyway or multiple keyway

# **Insert Position In Deg:**

150.0

### Shell Type:

#### **Connector Locking Method:**

Friction

#### **Connector Cable Strain Relief Method:**

Compression nut

#### **Terminal Location:**

Back single mating end all contact groupings

#### **Contact Material:**

Copper alloy single mating end all contact groupings

#### **Contact Surface Treatment:**

Gold single mating end all contact groupings

# NSN 5935-00-110-0248

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Rubber synthetic single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification all treatment responses
Included Contact Quantity:
7 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end 1st contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.013 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):