Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-110-0782

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Right angle, type
Overall Length:
Between 7.590 inches and 7.650 inches
Overall Height:
Between 0.530 inches and 0.550 inches
Body Width:
Between 0.516 inches and 0.526 inches
Distance Between Mounting Facility Centers:
Between 6.762 inches and 6.782 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end 1st contact grouping
Polarization Method:
Contact
Connector Locking Method:
Spring friction
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Side single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c, class 1 military specification single treatment response single mating end 1st contact grouping

Electrical Receptacle Connector - Page 2 of 2



Criticality Code Justification: Схср **Terminal Type:** Pin single mating end 1st contact grouping **Contact Material Specification:** Qq-c-533 federal specification single material response or qq-b-750 federal specification single material response single mating end 1st contact grouping **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end **Included Contact Quantity:** 25 single mating end 1st contact grouping **Included Contact Type:** Leaf spring single mating end 1st contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.025 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.
