Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-111-1881

Body Style:

Straight edge type w/mounting flange

Overall Length:

2.500 inches

Overall Height:

0.245 inches

Overall Width:

0.195 inches

Environmental Protection:

Shock resistant and vibration resistant and moisture resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

0.094 inches

Distance Between Mounting Facility Centers:

2.312 inches

Board Accommodated Length:

2.050 inches single board

Board Accommodated Width:

0.031 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.0 single mating end single contact grouping

Polarization Method:

Inter-contact polarizing keys

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

NSN 5935-00-111-1881

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.