Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-111-8420

Body Style: Straight shape **Overall Length:** 1.385 inches **Overall Height:** Between 1.146 inches and 1.170 inches **Overall Width:** Between 3.000 inches and 3.030 inches **Environmental Protection:** Salt spray proof and thermal shock resistant and vibration resistant and shock resistant and moisture resistant and solvent resistant and fuel resistant **Unthreaded Mounting Hole Diameter:** Between 0.192 inches and 0.202 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.558 inches and 0.566 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.570 inches and 2.580 inches **Distance From Mounting Shoulder To Front Face:** Between 0.519 inches and 0.534 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 51 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Mating end and guide pin/socket Shell Type: Solid **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -54.0 degrees celsius and 200.0 degrees celsius **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic single mating end and glass single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

NSN 5935-00-111-8420

Electrical Receptacle Connector - Page 2 of 2



| Terminal 1 | уре: |
|-------------|--|
| Crimp sing | le mating end single contact grouping |
| Contact M | aterial Specification: |
| Qq-c-533 f | ederal specification single material response single mating end single contact groupin |
| Guide Des | sign And Location: |
| D shape pi | n left-hand top at 6 oclock and d shape pin right-hand bottom at 6 oclock |
| Shell Mate | erial: |
| Aluminum | alloy 380.0 |
| Shell Surf | ace Treatment: |
| Nickel | |
| Shell Surf | ace Treatment Specification: |
| Mil-c-2607 | 4, cl 3 military specification single treatment response |
| Shell Mate | erial Specification: |
| Qq-a-591 f | ederal specification single material response |
| Included (| Contact Quantity: |
| 51 single n | nating end single contact grouping |
| Included (| Contact Type: |
| Round pin | single mating end single contact grouping |
| Precious I | Material And Location: |
| Contact su | rfaces gold |
| Precious I | Material And Weight: |
| 0.051 gold | grains, troy |
| Precious I | Material: |
| Gold | |
| Shelf Life: | |
| N/a | |
| Unit Of Me | easure: |
| | |
| Demilitaria | zation: |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (m | ilitary Standard): |
| Mil-g-4520 | 4 spec. |