Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-111-8436

Thread	Class:

2a

**Thread Direction:** 

Right-hand

## Body Style:

Straight shape

**Overall Length:** 

4.300 inches

#### **Overall Height:**

0.703 inches

**Overall Width:** 

0.360 inches

**Environmental Protection:** 

Moisture resistant and corrosion resistant and vibration resistant

Distance Between Mounting Facility Centers:

4.000 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

## **Connector Locking Method:**

Friction

Thready Qty Per Inch (tpi):

40

#### Thread Size:

0.112 inches

**Terminal Location:** 

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

# **Insert Material:**

Plastic diallyl phthalate single mating end

# Contact Surface Treatment Specification:

Mil-c-45204, type 2, class 1 military specification 1st treatment response single mating end single contact grouping and qq-s-365, type 2

federal specification 2nd treatment response single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Terminal Type	
	ng end single contact grouping
Contact Mater	ial Specification:
Qq-b-750, com	position b federal specification single material response single mating end single contact grouping
Insert Materia	I Specification:
Mil-m-14, type	sdi-5 military specification single material response single mating end
Included Cont	act Quantity:
37 single matin	ng end single contact grouping
Included Cont	act Type:
Round socket s	single mating end single contact grouping
Precious Mate	erial And Location:
Contact surface	es gold and contact surfaces silver
Precious Mate	erial And Weight:
0.037 gold grai	ns, troy and 0.037 silver grains, troy
Precious Mate	erial:
Gold and silver	
Thread Series	Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Measu	ire:
Demilitarizatio	on:
No	
Fiig:	
A039b0	
Mil-std (milita	ry Standard):
Mil-c-45204 sp	ec.