## NSN 5935-00-111-8439

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-111-8439

**Body Style:** 

Straight edge type

**Overall Length:** 

4.100 inches

**Overall Height:** 

0.984 inches

**Overall Width:** 

0.460 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.113 inches and 0.117 inches

**Distance Between Mounting Facility Centers:** 

3.700 inches

**Mating End Quantity:** 

1

**Contact Removability:** 

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:** 

7.0 single mating end 1st contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

500.0 single mating end 2nd contact grouping

**Contact Maximum Frequency Rating:** 

300.0 megahertz single mating end 2nd contact grouping

**Polarization Method:** 

Contact

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end 2nd contact grouping

**Terminal Location:** 

Back single mating end all contact groupings

**Contact Material:** 

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:** 

Gold single mating end all contact groupings and silver single mating end all contact groupings

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, class 1 military specification 1st treatment response single mating end all contact groupings and qq-s-365 type 2, grade b federal specification 2nd treatment response single mating end all contact groupings

**Terminal Type:** 

Pin single mating end all contact groupings

**Contact Material Specification:** 

Qq-b-750 federal specification single material response single mating end all contact groupings

**Insert Material Specification:** 

Mil-m-19833, type gdi-30 military specification single material response single mating end

## NSN 5935-00-111-8439

Electrical Receptacle Connector - Page 2 of 2



ncluded	Contact	Quantity:
---------	---------	-----------

36 single mating end 1st contact grouping

**Included Contact Type:** 

Round socket single mating end 1st contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.039 gold grains, troy and 0.039 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.