NSN 5935-00-112-3231

Steel

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-112-3231 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** Between 2.073 inches and 2.103 inches **Overall Height:** 0.426 inches **Overall Width:** Between 0.479 inches and 0.509 inches **Distance Between Mounting Facility Centers:** Between 1.847 inches and 1.857 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 25 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid Thread Size: 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:**

NSN 5935-00-112-3231

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium and chromate
Insert Material Specification:
Mil-m-19833, type gdi-30f military specification single material response single mating end
Included Contact Quantity:
25 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.025 gold grains, troy and 0.025 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0

Mil-std (military Standard):

Mil-m-19833 spec.