Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-113-2420

2aThread Direction:Right-handBody Style:Straight shape threadedOverall Length:1.063 inchesOverall Diameter:0.625 inchesDistance From Mounting Shoulder To Front Face:0.525 inchesMounting Facility Thickness:0.187 inchesThreaded Device Type:Mounting bushingMating End Quantity:1Contact Position Arrangement Style:Bnc single mating endContact Removability:Nonremovable single mating end single contact groupingShell Type:SolidEnnector Locking Method:Bayonet pin
Right-handBody Style:Straight shape threadedOverall Length:1.063 inchesOverall Diameter:0.625 inchesDistance From Mounting Shoulder To Front Face:0.525 inchesMounting Facility Thickness:0.187 inchesThreaded Device Type:Mounting bushingMating End Quantity:1Contact Position Arrangement Style:Bnc single mating endContact Removability:Nonremovable single mating end single contact groupingShell Type:SolidConnector Locking Method:
Body Style: Straight shape threaded Overall Length: 1.063 inches Overall Diameter: 0.625 inches Distance From Mounting Shoulder To Front Face: 0.525 inches Mounting Facility Thickness: 0.187 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Straight shape threaded Overall Length: 1.063 inches Overall Diameter: 0.625 inches Distance From Mounting Shoulder To Front Face: 0.525 inches Mounting Facility Thickness: 0.187 inches Threaded Device Type: 0.187 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 fortact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid
Overall Length:1.063 inchesOverall Diameter:0.625 inchesDistance From Mounting Shoulder To Front Face:0.525 inchesMounting Facility Thickness:0.187 inchesThreaded Device Type:Mounting bushingMating End Quantity:1Contact Position Arrangement Style:Bnc single mating endContact Removability:Nonremovable single mating end single contact groupingShell Type:SolidConnector Locking Method:
 1.063 inches Overall Diameter: 0.625 inches Distance From Mounting Shoulder To Front Face: 0.525 inches Mounting Facility Thickness: 0.187 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Overall Diameter:0.625 inchesDistance From Mounting Shoulder To Front Face:0.525 inchesMounting Facility Thickness:0.187 inchesThreaded Device Type:Mounting bushingMating End Quantity:1Contact Position Arrangement Style:Bnc single mating endContact Removability:Nonremovable single mating end single contact groupingShell Type:SolidConnector Locking Method:
0.625 inches Distance From Mounting Shoulder To Front Face: 0.525 inches Mounting Facility Thickness: 0.187 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Distance From Mounting Shoulder To Front Face: 0.525 inches Mounting Facility Thickness: 0.187 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
0.525 inches Mounting Facility Thickness: 0.187 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Mounting Facility Thickness: 0.187 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
0.187 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Mating End Quantity: 1 Contact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
1 Contact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Contact Position Arrangement Style: Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Bnc single mating end Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Contact Removability: Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Nonremovable single mating end single contact grouping Shell Type: Solid Connector Locking Method:
Shell Type: Solid Connector Locking Method:
Solid Connector Locking Method:
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
28
Thread Size:
0.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 1 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round Included Contact Type: Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact surface gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0