## NSN 5935-00-113-2500

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-113-2500 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 0.490 inches **Overall Diameter:** 0.325 inches **Distance From Mounting Shoulder To Front Face:** 0.365 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 93.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 32 Thread Size: 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

Silver alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy

## NSN 5935-00-113-2500

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantit	ty:
--------------------------	-----

1 single mating end single contact grouping

**Included Contact Type:** 

Coaxial socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.055 gold grains, troy

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0