

View Online at <https://aerobasegroup.com/nsn/5935-00-113-4923>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Electrical Insulation Feature:**

Insulated completely

**Identification Code Color:**

Black

**Body Style:**

Threaded bushing mounted

**Overall Length:**

1.000 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.625 inches

**Overall Diameter:**

0.405 inches

**Bushing Accommodation Hole Shape:**

Round w/flat

**Maximum Voltage Rating In Volts:**

750.0 ac

**Accommodated Finger Type:**

Test prod single finger

**Finger Accommodation Diameter:**

0.080 inches single finger

**Finger Accommodation Length:**

0.375 inches single finger

**Bushing Thru-hole Accommodation Diameter:**

0.255 inches

**Bushing Thru-hole Accommodation Length:**

0.238 inches

**Bushing Thru-hole Accommodation Width:**

Between 0.250 inches and 0.255 inches

**Capacitance In Picofarads:**

15.0

**Mounting Facility Type And Quantity:**

1 bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.250 inches

**Terminal Type:**

Tab, solder lug

**Special Features:**

With uninsulated chain

**Material:**

Plastic, polyamide insulator

**Material:**

Plastic polyamide insulator

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Surface Treatment:**

Nickel terminal

**Surface Treatment:**

Nickel terminal

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A03400