

View Online at <https://aerobasegroup.com/nsn/5935-00-113-4923>

Thread Class:

2a

Thread Direction:

Right-hand

Electrical Insulation Feature:

Insulated completely

Identification Code Color:

Black

Body Style:

Threaded bushing mounted

Overall Length:

1.000 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.625 inches

Overall Diameter:

0.405 inches

Bushing Accommodation Hole Shape:

Round w/flat

Maximum Voltage Rating In Volts:

750.0 ac

Accommodated Finger Type:

Test prod single finger

Finger Accommodation Diameter:

0.080 inches single finger

Finger Accommodation Length:

0.375 inches single finger

Bushing Thru-hole Accommodation Diameter:

0.255 inches

Bushing Thru-hole Accommodation Length:

0.238 inches

Bushing Thru-hole Accommodation Width:

Between 0.250 inches and 0.255 inches

Capacitance In Picofarads:

15.0

Mounting Facility Type And Quantity:

1 bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.250 inches

Terminal Type:

Tab, solder lug

Special Features:

With uninsulated chain

Material:

Plastic, polyamide insulator

Material:

Plastic polyamide insulator

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Surface Treatment:

Nickel terminal

Surface Treatment:

Nickel terminal

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03400