

View Online at <https://aerobasegroup.com/nsn/5935-00-113-7428>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

Between 0.974 inches and 0.994 inches

**Overall Height:**

Between 3.927 inches and 3.947 inches

**Overall Width:**

Between 3.365 inches and 3.385 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.995 inches and 1.005 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 2.870 inches and 2.880 inches

**Distance From Mounting Shoulder To Front Face:**

0.750 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

78 all mating ends

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

10.0 all mating ends all contact groupings

**Polarization Method:**

2 polarization posts

**Shell Type:**

Solid

**Connector Locking Method:**

Screw

**Thready Qty Per Inch (tpi):**

12

**Thread Size:**

0.312 inches

**Terminal Location:**

Back all mating ends all contact groupings

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

**Insert Material:**

Plastic diallyl phthalate all mating ends

**Terminal Type:**

Crimp all mating ends all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Type:**

Round socket single mating end single contact grouping

**Special Features:**

Polarized at position v

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.156 gold grains, troy and 0.156 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0