Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-113-9257

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
1.990 inches
Overall Diameter:
1.980 inches
Environmental Protection:
Thermal shock resistant and vibration resistant and moisture resistant
Cable Entrance Diameter:
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
•
Contact Position Arrangement Style:
28-21 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Thread Length:
0.718 inches
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius

Electrical Plug Connector - Page 2 of 2



Featu	Ires Provided:
Close	d entry contact
Threa	ady Qty Per Inch (tpi):
18	
Threa	ad Size:
1.750	inches
Term	inal Location:
Back	single mating end single contact grouping
Conta	act Material:
Copp	er alloy single mating end single contact grouping
Conta	act Surface Treatment:
Silver	single mating end single contact grouping
Inser	t Material:
Rubb	er synthetic single mating end
Conta	act Surface Treatment Specification:
Qq-s-	365 federal specification single treatment response single mating end single contact grouping
Crim	ping Tool Identifying Number:
71468	3-ms3191-1
Term	inal Type:
Crimp	o single mating end single contact grouping
Shell	Material:
Alumi	num alloy
Shell	Surface Treatment:
Cadm	nium and chromate
Inclu	ded Contact Quantity:
37 sir	ngle mating end single contact grouping
Inclu	ded Contact Type:
Roun	d socket single mating end single contact grouping
Preci	ous Material And Location:
Conta	act surfaces silver
Preci	ous Material And Weight:
0.037	silver grains, troy
Preci	ous Material:
Silver	
Threa	ad Series Designator:
Uns	
Shelf	Life:
N/a	
Unit (Of Measure:
Demi	litarization:
No	
Fiig:	
A0391	b0