NSN 5935-00-114-0721

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-114-0721

View Online at https://aerobasegroup.com/nsn/5935-00-114-0721
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.532 inches
Overall Height:
Between 1.485 inches and 1.515 inches
Overall Width:
Between 1.485 inches and 1.515 inches
Unthreaded Mounting Hole Diameter:
Between 0.118 inches and 0.124 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.151 inches and 1.161 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.151 inches and 1.161 inches
Distance From Mounting Shoulder To Front Face:
Between 0.750 inches and 0.760 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20-27 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
660.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
940.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches Thready Oty Per Inch (toi):
Thready Qty Per Inch (tpi):

18

NSN 5935-00-114-0721 Electrical Receptacle Connector - Page 2 of 2



Thread Size:
1.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2 federal specification single treatment response
Insert Material Specification:
Mil-r-3065 military specification single material response single mating end
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.014 gold grains, troy and 0.014 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-r-3065 spec.