NSN 5935-00-114-0724

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-114-0724 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Height:** 1.625 inches **Overall Width:** 1.625 inches **Environmental Protection:** Weatherproof **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.130 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** "3, 5-15" single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 15.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 110.0 single mating end all contact groupings **Polarization Method:** Contact **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell **Thread Size:** 1.375 inches

Terminal Location:

Back single mating end all contact groupings

NSN 5935-00-114-0724 Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end all contact groupings
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Included Contact Quantity:
2 single mating end 2nd contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0