NSN 5935-00-114-1564

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-114-1564 **Thread Class:** 2a and 2a **Thread Direction:** Left-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.654 inches **Overall Diameter:** Between 2.355 inches and 2.396 inches **Environmental Protection:** Waterproof and explosion proof and corrosion resistant and vibration resistant and shock resistant **Distance From Mounting Shoulder To Front Face:** Between 0.703 inches and 0.719 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 32-64 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 200.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 250.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 16 and 10 **Thread Size:**

2.062 inches and 2.250 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-114-1564

A039b0

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Included Contact Quantity:
54 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Solder flange mtd
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.054 gold grains, troy and 0.054 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Uns and double stub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: