

View Online at <https://aerobasegroup.com/nsn/5935-00-114-4920>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape

**Overall Length:**

Between 0.974 inches and 0.994 inches

**Overall Height:**

Between 3.927 inches and 3.947 inches

**Overall Width:**

Between 3.365 inches and 3.385 inches

**Unthreaded Mounting Hole Diameter:**

0.144 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.995 inches and 1.005 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 2.870 inches and 2.880 inches

**Distance From Mounting Shoulder To Front Face:**

0.750 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

78 all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Contact Maximum Current Rating In Amps:**

10.0 all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Screw

**Thready Qty Per Inch (tpi):**

16

**Thread Size:**

0.312 inches

**Terminal Location:**

Back all mating ends single contact grouping

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold and silver all mating ends single contact grouping

**Insert Material:**

Plastic diallyl phthalate all mating ends

**Terminal Type:**

Crimp all mating ends single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Type:**

Round socket all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.156 gold grains, troy and 0.156 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Un

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0