Electrical Receptacle Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-114-5622

Th	nread Class:
2a	L Contraction of the second
Th	nread Direction:
Ri	ght-hand
Вс	ody Style:
St	raight shape, external coupling
0\	verall Length:
1.5	532 inches
0\	verall Height:
Be	etween 1.360 inches and 1.390 inches
0\	verall Width:
Be	etween 1.360 inches and 1.390 inches
Ur	nthreaded Mounting Hole Diameter:
Be	etween 0.118 inches and 0.124 inches
Ce	enter To Center Distance Between Mounting Facilities Parallel To Height:
Be	etween 1.057 inches and 1.067 inches
Di	stance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Be	etween 1.057 inches and 1.067 inches
Di	stance From Mounting Shoulder To Front Face:
Be	etween 0.750 inches and 0.760 inches
Th	readed Device Type:
Сс	pupling facility
Ma	ating End Quantity:
1	
Сс	ontact Position Arrangement Style:
18	-4 single mating end
Co	ontact Removability:
Re	emovable single mating end single contact grouping
Co	ontact Maximum Current Rating In Amps:
22	.0 single mating end single contact grouping
Co	ontact Maximum Ac Voltage Rating In Volts:
66	0.0 single mating end single contact grouping
Co	ontact Maximum Dc Voltage Rating In Volts:
94	0.0 single mating end single contact grouping
Sh	nell Type:
Sc	blid
Co	onnector Locking Method:
Ex	ternally threaded shell
Th	aread Length:
0.6	625 inches
Th	nready Qty Per Inch (tpi):
18	

NSN 5935-00-114-5622

Electrical Receptacle Connector - Page 2 of 2



Thread Size: 1.125 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2 federal specification single treatment response **Insert Material Specification:** Mil-r-3065 military specification single material response single mating end **Included Contact Quantity:** 4 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.004 gold grains, troy and 0.004 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-r-3065 spec.