

View Online at <https://aerobasegroup.com/nsn/5935-00-114-8847>

Body Style:

Straight shape, flange mount, external coupling

Overall Length:

1.383 inches

Overall Height:

1.125 inches

Overall Width:

1.125 inches

Environmental Protection:

Vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.994 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.994 inches

Distance From Mounting Shoulder To Front Face:

0.431 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

14-19 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

165.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Potting type

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

19 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0