# NSN 5935-00-115-1960

Gold and silver

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-115-1960

Body Style:
Straight shape, internal coupling
Overall Length:
0.750 inches
Overall Diameter:
0.375 inches
Environmental Protection:
Weatherproof
Cable Entrance Diameter:
0.105 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Dm single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
180.0 and 180.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Cable clamp
Radio Frequency Type Contact Characteristic Impedance In Ohms:
70.0 single mating end single contact grouping
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Pin single mating end single contact grouping
Shell Material:
Copper alloy
Shall Surface Treatment:

## NSN 5935-00-115-1960

Electrical Plug Connector - Page 2 of 2



#### **Included Contact Quantity:**

1 single mating end single contact grouping

#### **Included Contact Type:**

Coaxial pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact and body surfaces gold and contact and body surfaces silver

### **Precious Material And Weight:**

0.105 gold grains, troy and 0.105 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A039b0