## NSN 5935-00-115-5360

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-115-5360 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight type **Overall Length:** 3.250 inches **Overall Height:** 1.000 inches **Overall Width:** 0.871 inches **Unthreaded Mounting Hole Diameter:** 0.112 inches **Distance Between Mounting Facility Centers:** 2.871 inches **Threaded Device Type:** Mounting hole **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 800.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

oomao mato lan

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and silver single mating end single contact grouping

## NSN 5935-00-115-5360

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:
Metal
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.024 gold grains, troy and 0.024 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0