

View Online at <https://aerobasegroup.com/nsn/5935-00-116-2712>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

2.502 inches

Overall Height:

0.656 inches

Overall Width:

1.346 inches

Environmental Protection:

Dripproof and vibration resistant

Distance Between Mounting Facility Centers:

1.969 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

66 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

545.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

762.0 single mating end single contact grouping

Polarization Method:

JackscREW

Shell Type:

Solid

Connector Locking Method:

JackscREW-socket

Thready Qty Per Inch (tpi):

40 and 40 and 40

Thread Size:

0.112 inches and 0.112 inches and 0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Anodize

Included Contact Quantity:

66 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.066 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0