Unable to decode and unable to decode

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-116-8210

Body Style:
Right angle type
Overall Length:
1.600 inches
Overall Width:
0.176 inches
Body Height:
0.113 inches
Unthreaded Mounting Hole Diameter:
0.052 inches
Distance Between Mounting Facility Centers:
1.400 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1350.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Cable Strain Relief Method:
Bracket
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14f, ty sdg-f military specification single material response single mating end
Unable To Decode:

NSN 5935-00-116-8210

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

12 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.012 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14f spec.