NSN 5935-00-116-8912

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-116-8912

Body Style:
Straight shape
Overall Length:
3.844 inches
Overall Height:
0.562 inches
Overall Width:
0.438 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
3.500 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Shell Type: Solid
Solid
Solid Connector Locking Method:
Solid Connector Locking Method: Spring friction
Solid Connector Locking Method: Spring friction Terminal Location:
Solid Connector Locking Method: Spring friction Terminal Location: Back single mating end single contact grouping
Solid Connector Locking Method: Spring friction Terminal Location: Back single mating end single contact grouping Contact Material:
Solid Connector Locking Method: Spring friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Solid Connector Locking Method: Spring friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Solid Connector Locking Method: Spring friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Solid Connector Locking Method: Spring friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type:
Solid Connector Locking Method: Spring friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Tapered pin single mating end single contact grouping
Solid Connector Locking Method: Spring friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Tapered pin single mating end single contact grouping Shell Material:
Solid Connector Locking Method: Spring friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Tapered pin single mating end single contact grouping Shell Material: Aluminum alloy
Solid Connector Locking Method: Spring friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Tapered pin single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment:
Solid Connector Locking Method: Spring friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Tapered pin single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium
Solid Connector Locking Method: Spring friction Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Tapered pin single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium Included Contact Quantity:

Contact surfaces gold

Precious Material And Location:

NSN 5935-00-116-8912

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weig	ht:
----------------------------	-----

0.015 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0