NSN 5935-00-118-3882

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-118-3882 **Body Style:** Straight shape **Overall Length:** 2.088 inches **Overall Height:** 0.623 inches **Overall Width:** 0.494 inches **Environmental Protection:** Shock proof and thermal shock resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 1.852 inches **Mating End Quantity: Contact Position Arrangement Style:** 25 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Steel **Shell Surface Treatment:**

Cadmium

Included Contact Quantity:

25 single mating end single contact grouping

NSN 5935-00-118-3882

Electrical Receptacle Connector - Page 2 of 2



Inc	luded	d Con	tact	Type:
	IUUC	4 O OH	ıavı	IVDC.

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.025 gold grains, troy and 0.025 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

26581-340691-5 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0