

View Online at <https://aerobasegroup.com/nsn/5935-00-118-7862>

Thread Class:

2a

Thread Direction:

Right-hand

Electrical Insulation Feature:

Insulated completely

Identification Code Color:

Gray

Body Style:

Threaded bushing mounted

Overall Length:

Between 0.850 inches and 0.910 inches

Mounting Bushing Length:

Between 0.425 inches and 0.445 inches

Body Length:

Between 0.620 inches and 0.640 inches

Overall Diameter:

Between 0.280 inches and 0.340 inches

Bushing Accommodation Hole Shape:

Round w/flat

Maximum Voltage Rating In Volts:

1500.0 dc

Accommodated Finger Type:

Test prod single finger

Finger Accommodation Diameter:

0.094 inches and 0.114 inches single finger

Finger Accommodation Length:

0.600 inches and 0.660 inches single finger

Bushing Thru-hole Accommodation Length:

Between 0.224 inches and 0.244 inches

Bushing Thru-hole Accommodation Width:

Between 0.240 inches and 0.260 inches

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

1 bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.164 inches

Terminal Type:

Turret

Material:

Ceramic insulator

Material:

Plastic polycarbonate cap

Precious Material And Location:

Contact surface gold

Precious Material:

Gold

Surface Treatment:

Gold contact

Surface Treatment:

Gold contact

Thread Series Designator:

Unc

Specification Data:

06481-952494 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400