## NSN 5935-00-118-7865

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-118-7865 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Yellow **Body Style:** Threaded bushing mounted **Overall Length:** 0.880 inches **Mounting Bushing Length:** 0.435 inches **Body Length:** 0.630 inches **Overall Diameter:** 0.310 inches **Bushing Accommodation Hole Shape:** Round w/flat **Maximum Voltage Rating In Volts:** 1500.0 dc **Accommodated Finger Type:** Banana spring single finger **Finger Accommodation Diameter:** 0.104 inches single finger **Finger Accommodation Length:** 0.630 inches single finger **Bushing Thru-hole Accommodation Length:** 0.234 inches **Bushing Thru-hole Accommodation Width:** 0.250 inches **Current Rating In Amps:** 5.0 **Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 

0.164 inches

Terminal Type:

Turret

## NSN 5935-00-118-7865

Tip Jack - Page 2 of 2



Material:
Ceramic insulator
Material:
Plastic polycarbonate cap
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.001 gold grains, troy
Precious Material:
Gold
Surface Treatment:
Gold contact
Surface Treatment:
Gold contact
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A03400