NSN 5935-00-119-3206

Thread Class:

Right-hand **Body Style:**

Thread Direction:

Overall Length: 0.750 inches Overall Width:

Straight shape, latching

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-119-3206

0.680 inches
Diameter:
0.460 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
B4s single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Detent
Thready Qty Per Inch (tpi):
24
Thread Size:
0.375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Insert Material Specification:
Mil-m-19833- ty gdi-30 military specification single material response single mating end

NSN 5935-00-119-3206

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
4 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/double flat
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.004 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-m-19833- spec.

A039b0