## NSN 5935-00-119-7325

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-119-7325

**Body Style:** 

Straight edge type w/card guide

**Overall Length:** 

6.300 inches

Overall Width:

Between 0.245 inches and 0.250 inches

**Body Height:** 

0.187 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant

**Board Accommodated Length:** 

6.100 inches single board

**Board Accommodated Width:** 

Between 0.066 inches and 0.072 inches

**Mating End Quantity:** 

1

## **Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Polarization Method:** 

Fixed contact to contact

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Pin single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-613, comp 2 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

120 single mating end single contact grouping

**Included Contact Type:** 

Spring pincers single mating end single contact grouping

## NSN 5935-00-119-7325

Electrical Receptacle Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
Precious Material And Weight:
0.120 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.