Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-119-8995

Body Style: Straight edge type **Overall Length:** Between 1.740 inches and 1.800 inches **Overall Width:** Between 0.328 inches and 0.358 inches **Environmental Protection:** Moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.145 inches **Distance Between Mounting Facility Centers:** Between 1.521 inches and 1.541 inches **Board Accommodated Length:** 1.093 inches single board and 1.103 inches single board **Board Accommodated Width:** Between 0.054 inches and 0.070 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Bridged contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys Shell Type: Solid **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Pin single mating end single contact grouping **Insert Material Specification:** Mil-m-19833 ty gdi-30f military specification single material response single mating end **Included Contact Quantity:** 47 single mating end single contact grouping



Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.047 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-21097/13 government specification

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0

Mil-std (military Standard):

Mil-m-19833 spec.