

View Online at <https://aerobasegroup.com/nsn/5935-00-122-0024>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.438 inches

Overall Diameter:

1.156 inches

Environmental Protection:

Salt water resistant and moisture resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

14s-2 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

200.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Potting

Connector Locking Method:

Internally threaded coupling nut

Connector Cable Strain Relief Method:

Potting type

Thread Size:

0.875 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

4 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0