## NSN 5935-00-124-0038

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-124-0038 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/flange **Overall Length:** 1.305 inches **Overall Height:** 0.688 inches **Overall Width:** 0.688 inches **Environmental Protection:** Weatherproof **Unthreaded Mounting Hole Diameter:** 0.128 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.490 inches and 0.510 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.490 inches and 0.510 inches **Distance From Mounting Shoulder To Front Face:** 0.703 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 2 **Contact Position Arrangement Style:** Tnc all mating ends **Contact Removability:** 

Nonremovable all mating ends all contact groupings

Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends all contact groupings

**Thread Size:** 

0.438 inches

**Insert Material:** 

Plastic polytetrafluoroethylene all mating ends

**Shell Material:** 

Plastic polytetrafluoroethylene

# NSN 5935-00-124-0038

Connector Adapter - Page 2 of 2



Mil-p-19468 military specification single material response

### **Insert Material Specification:**

Mil-p-19468 military specification single material response all mating ends

### **Included Contact Quantity:**

1 2nd mating end all contact groupings

### **Included Contact Type:**

Coaxial socket all mating ends all contact groupings

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19468 spec.