NSN 5935-00-124-5262

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-124-5262

Body Style:

Straight edge type

Overall Length:

Between 1.490 inches and 1.510 inches

Overall Height:

Between 0.645 inches and 0.675 inches

Overall Width:

Between 0.245 inches and 0.255 inches

Environmental Protection:

Humidity resistant and corrosion resistant and shock resistant and vibration resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

Between 0.128 inches and 0.132 inches

Distance Between Mounting Facility Centers:

Between 1.245 inches and 1.255 inches

Board Accommodated Length:

0.937 inches single board and 0.938 inches single board

Board Accommodated Width:

Between 0.027 inches and 0.037 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -53.0 degrees celsius and 68.3 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, cl 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

NSN 5935-00-124-5262

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-p-19833, ty gdi-30f military specification single material response single mating end

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.014 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.