NSN 5935-00-125-0938

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-125-0938 **Body Style:** Straight shape, flush mount **Overall Length:** 1.109 inches **Overall Height:** 3.375 inches **Overall Width:** 1.687 inches **Unthreaded Mounting Hole Diameter:** 0.152 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.875 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** 1.000 inches **Distance From Mounting Shoulder To Front Face:** 0.062 inches **Mating End Quantity: Contact Position Arrangement Style:** 78 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1000.0 single mating end single contact grouping **Polarization Method:** Contact Shell Type: Solid **Connector Locking Method: Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:**

Crimp single mating end single contact grouping

NSN 5935-00-125-0938

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
78 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
$0.078 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.078 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0