NSN 5935-00-125-7014

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-125-7014

| Body Style: |
|---|
| Straight shape |
| Overall Length: |
| 0.925 inches |
| Overall Height: |
| 1.365 inches |
| Overall Width: |
| 0.205 inches |
| Environmental Protection: |
| Vibration resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.092 inches |
| Distance Between Mounting Facility Centers: |
| 0.715 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 15 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end single contact grouping |
| Polarization Method: |
| Mating end |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Included Contact Quantity: |
| 15 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Precious Material And Location: |
| |
| Contact and terminal surfaces gold |
| Contact and terminal surfaces gold Precious Material And Weight: |
| • |

Gold

NSN 5935-00-125-7014

Electrical Receptacle Connector - Page 2 of 2



| She | lf | Life: | |
|------|----|-------|--|
| Oile | •• | LIIV. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0