

View Online at <https://aerobasegroup.com/nsn/5935-00-126-5937>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape w/cable clamp

**Overall Length:**

1.672 inches

**Bushing Diameter:**

0.630 inches

**Overall Height:**

Between 0.985 inches and 1.000 inches

**Overall Width:**

Between 0.985 inches and 1.000 inches

**Environmental Protection:**

Corrosion resistant and vibration resistant and shock resistant and thermal shock resistant and moisture resistant

**Unthreaded Mounting Hole Diameter:**

0.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 0.713 inches and 0.723 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.713 inches and 0.723 inches

**Cable Entrance Diameter:**

Between 0.468 inches and 0.470 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.641 inches and 0.671 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

N single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1000.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:**

11000.0 megahertz single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thread Length:**

0.187 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204 type 2, cl 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Silver

**Shell Surface Treatment Specification:**

Qq-s-365 type 2, grade b federal specification single treatment response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Special Features:**

Modified compression nut and clamp

**Precious Material And Location:**

Contact surface gold and shell surface silver

**Precious Material And Weight:**

0.005 gold grains, troy and 0.100 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.