NSN 5935-00-128-6004

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-128-6004

Body Style:
Straight shape
Overall Height:
2.000 inches
Overall Width:
0.875 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.688 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.468 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
8.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Screw
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type sdctkl1ajdamil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
38 single mating end single contact grouping
Included Contact Type:
Hermaphrodite single mating end single contact grouping

Special Features:

Center locknut coupling, male insert type

NSN 5935-00-128-6004

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.038 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.