NSN 5935-00-128-8134

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-128-8134 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 3.875 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 3.500 inches **Overall Height:** 1.600 inches **Overall Width:** 2.000 inches **Environmental Protection:** Vibration resistant and shock resistant **Unthreaded Mounting Hole Diameter:** 0.150 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 25-104 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end single contact grouping **Polarization Method:** Jackscrew and shell **Shell Type:** Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 32

Thread Size:

0.164 inches

NSN 5935-00-128-8134

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Insert Material Specification:
Mil-p-14, ty mfe military specification single material response single mating end
Shell Guide Type And Location Designator:
C slot
Included Contact Quantity:
104 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.104 gold grains, troy and 0.104 silver grains, troy
3 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3 - 3 -
Precious Material:
Precious Material:
Precious Material: Gold and silver
Precious Material: Gold and silver Thread Series Designator:
Precious Material: Gold and silver Thread Series Designator: Unc
Precious Material: Gold and silver Thread Series Designator: Unc Shelf Life:
Precious Material: Gold and silver Thread Series Designator: Unc Shelf Life: N/a
Precious Material: Gold and silver Thread Series Designator: Unc Shelf Life: N/a
Precious Material: Gold and silver Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:
Precious Material: Gold and silver Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:
Precious Material: Gold and silver Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No
Precious Material: Gold and silver Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: