NSN 5935-00-129-6553

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-129-6553 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Right angle type **Overall Length:** Between 1.765 inches and 1.785 inches **Body Width:** 0.250 inches **Body Height:** 0.375 inches **Distance Between Mounting Facility Centers:** 1.300 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 2.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 500.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:**

Tab, solder lug single mating end single contact grouping

Included Contact Quantity:

10 single mating end single contact grouping

NSN 5935-00-129-6553

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Bifurcated spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0