

NSN 5935-00-130-2597 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-130-2597 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Right angle, type **Overall Length:** Between 7.590 inches and 7.650 inches **Overall Height:** Between 0.530 inches and 0.550 inches **Body Width:** Between 0.516 inches and 0.526 inches **Distance Between Mounting Facility Centers:** Between 6.762 inches and 6.782 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end 1st contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end 1st contact grouping **Polarization Method:** Contact **Connector Locking Method:** Spring friction Thready Qty Per Inch (tpi): 40

Thread Size:

0.112 inches

Terminal Location:

Side single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, grade c, class 1 military specification single treatment response single mating end 1st contact grouping

NSN 5935-00-130-2597

Criticality Code Justification:

Electrical Receptacle Connector - Page 2 of 2



| Схср |
|--|
| Terminal Type: |
| Pin single mating end 1st contact grouping |
| Contact Material Specification: |
| Qq-c-533 federal specification single material response or qq-b-750 federal specification single material response single mating end 1st |
| contact grouping |
| Insert Material Specification: |
| Mil-m-14, type sdg-f military specification single material response single mating end |
| Included Contact Quantity: |
| 24 single mating end 1st contact grouping |
| Included Contact Type: |
| Leaf spring single mating end 1st contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.024 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |
| Mil-g-45204 spec. |
| |
| |