

View Online at <https://aerobasegroup.com/nsn/5935-00-130-2598>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Right angle, type

**Overall Length:**

Between 7.590 inches and 7.650 inches

**Overall Height:**

Between 0.530 inches and 0.550 inches

**Body Width:**

Between 0.516 inches and 0.526 inches

**Distance Between Mounting Facility Centers:**

Between 6.762 inches and 6.782 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end 1st contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end 1st contact grouping

**Polarization Method:**

Contact

**Connector Locking Method:**

Spring friction

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Terminal Location:**

Side single mating end 1st contact grouping

**Contact Material:**

Copper alloy single mating end 1st contact grouping

**Contact Surface Treatment:**

Gold single mating end 1st contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type ii, grade c, class 1 military specification single treatment response single mating end 1st contact grouping

**Terminal Type:**

Pin single mating end 1st contact grouping

**Contact Material Specification:**

Qq-c-533 federal specification single material response or qq-b-750 federal specification single material response single mating end 1st contact grouping

**Insert Material Specification:**

Mil-m-14, type sgd-f military specification single material response single mating end

**Included Contact Quantity:**

23 single mating end 1st contact grouping

**Included Contact Type:**

Leaf spring single mating end 1st contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.023 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.