## NSN 5935-00-131-0732

Plug-in Electronic Components Socket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-131-0732 **Body Material:** Plastic **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Top mount w/studs **Fabrication Method:** Molded **Overall Length:** 1.719 inches **Tempurature Rating:** -65.0 degrees celsius and 125.0 degrees celsius **Overall Height:** 0.625 inches **Overall Width:** 0.500 inches **Mounting Hole Diameter:** 0.125 inches **Body Mounting Hole Accommodation Length:** 1.078 inches **Body Mounting Hole Accommodation Width:** 0.516 inches **Distance Between Mounting Facility Centers:** 1.406 inches **Mounting Hole Style:** Rectangular, w/two mounting holes/slots **Specific Equipment Accommodated:** Relay **Contact Maximum Current Rating In Amps: Contact Material:** Phosphor bronze **Contact Surface Treatment:** Gold and silver **Accommodated Contact Quantity:** 8 **Thread Length:** 0.250 inches

**Projection Length Below Mounting Surface:** 

0.344 inches

## NSN 5935-00-131-0732

Plug-in Electronic Components Socket - Page 2 of 2



Mounting Method:
Threaded stud
Mounting Type For Which Designed:
Chassis
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Contact Position Arrangement Style:
Dual in line
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.008 gold grains, troy and 0.008 silver grains, troy
Thread Series Designator:
Unc
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A02300