

View Online at <https://aerobasegroup.com/nsn/5935-00-131-0798>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

0.671 inches

Overall Diameter:

0.375 inches

Environmental Protection:

Moisture resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

0.431 inches

Mounting Facility Thickness:

0.093 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

1.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

400.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

10000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thready Qty Per Inch (tpi):

32 and 32

Thread Size:

0.190 inches and 0.190 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Turret single mating end single contact grouping

Contact Material Specification:

Qq-b-626, comp 22 federal specification single material response single mating end single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204, type 2 cl 2 military specification single treatment response

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Coaxial pin single mating end single contact grouping

Special Features:

Hermetically sealed

Precious Material And Location:

Contact surface and shell surface gold

Precious Material And Weight:

0.101 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf and unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.