

View Online at <https://aerobasegroup.com/nsn/5935-00-131-0799>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.906 inches

**Overall Diameter:**

0.406 inches

**Cable Entrance Diameter:**

0.090 inches

**Distance From Mounting Shoulder To Front Face:**

0.375 inches

**Mounting Facility Thickness:**

0.219 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

400.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Spring friction

**Connector Cable Strain Relief Method:**

Compression nut

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

**Insert Material:**

Plastic polytetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, class 2 military specification 1st treatment response single mating end single contact grouping and mil-c-145501 military specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Tapered pin single mating end single contact grouping

**Contact Material Specification:**

Qq-c-530, heat treated federal specification single material response single mating end single contact grouping and qq-b-626, comp 22 1/2 h federal specification single material response single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold and copper

**Shell Surface Treatment Specification:**

Mil-g-45204, class 2 military specification 1st treatment response and mil-c-14550 military specification 2nd treatment response

**Insert Material Specification:**

Mil-m-14077 military specification single material response single mating end

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact and shell surfaces gold

**Precious Material And Weight:**

0.105 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.